

# HUSH FILL 60 HEAVY PUGGING



Hush Fill 60 Heavy Pugging is a granular mineral filler specifically designed to meet the required density of 80kgs/m<sup>2</sup> at the 60mm regulation depth specified within UK Building Regulations for sound insulation between timber floor joists.

## SAFETY

Joist loadings must always be checked by a structural engineer prior to specification or use. Hush-Fill 60 must never be installed directly onto a plasterboard or lath and plaster ceiling, supporting shelves should be constructed – see fitting instructions available online at [www.hush.acoustics.co.uk](http://www.hush.acoustics.co.uk)

Hush-Fill 60 tubes weigh approximately 25kg each and care must be taken when manually handling and lifting.

## ACOUSTIC PERFORMANCE

Impact L' <sub>nT,w</sub> dB	Airborne D <sub>nT,w</sub> dB	Airborne D <sub>nT,w</sub> + C <sub>tr</sub> dB
48	64	53

Results based on Hush-System 1 test results



## SUITABLE FOR:



## PRODUCT DATA

- Application in between joists, supported by plywood screwed to the underside of the joists or on a shelf constructed between the joists. Joist loadings must be checked by a qualified person prior to specification.
- Comprises 2-10mm dry mineral fill, packed in sealed polythene tubes.
- Tube Dimensions Approx. 1100mm long x 150mm diameter
- Weight per m<sup>2</sup> - 80 kgs at required 60mm depth for UK Building Regulations
- Weight per tube Approx. 25 kgs
- Overall nominal thickness - 60mm at required depth for UK Building Regulations (3.2 tubes per m<sup>2</sup>)

## FEATURES

- ✓ Traditional method ideal for restricted projects such as upgrading listed buildings
- ✓ Allows all work to be carried out from above
- ✓ Building Regulations Part E (England and Wales), Section 5 (Scotland) and Part G (Northern Ireland)
- ✓ Easy and accurate installation
- ✓ Traditional method of reducing the transmission of airborne sound between timber separating floors within refurbishment projects
- ✓ Upgrades the airborne performance of separating floors whilst allowing decorative lath and plaster ceilings to remain intact

## HUSH ACOUSTICS

TEL: 0151 933 2026

EMAIL: [info@hushacoustics.co.uk](mailto:info@hushacoustics.co.uk)

[www.hushacoustics.co.uk](http://www.hushacoustics.co.uk)

 [hush-acoustics](https://www.linkedin.com/company/hush-acoustics)

 [@hushacoustics](https://twitter.com/hushacoustics)  [hushuk.acoustics](https://www.facebook.com/hushuk.acoustics)

44 Canal Street, Bootle, Liverpool L20 8QU  
Offices also based in London and Yorkshire



**HUSH ACOUSTICS**