

HUSH ISOLATION TAPE



Hush Heavy Duty Isolation Tape has been designed as an isolating layer to be used under timber/metal stud walls or on top of floor joists.

It is imperative to isolate joist tops, the header/sole plates of stud construction and seal all wall linings to break sound transmission paths. Hush Heavy Duty Isolation Tape can be used for all these applications and is self adhesive one side.

Hush Acoustics have noticed that acoustic testing can fail due to noise transmission down internal partitions. By isolating the sole and header plates from the construction with the Hush isolation tape this issue is removed.

ACOUSTIC PERFORMANCE

To be used to ensure that flanking/direct transmission of sound, through partitions, does not effect the compliance with UK Building Regulations



PRODUCT DATA

- To be used to isolate sole and header plates of timber/metal stud walls or at the perimeter junctions of the Hush Wall System.
- Self-adhesive foam/rubber tape which is easily installed.
- Improves acoustic performance in stud wall construction.
- Isolates chipboard, plywood or original floorboards from the structural timber joists.
- 10m rolls. Comes in 50mm and 100mm widths.
- Nominal 8mm thick.

FEATURES

- ✓ Self Adhesive backing to one side making it very simply and easy to install
- ✓ Helps to reduce flanking and direct sound transmission through metal and timber stud walls
- ✓ Helps for compliance for all UK Building Regulations for sound transmission
- ✓ Helps achieve Code For Sustainable Homes compliance
- ✓ 50mm and 100mm widths
- ✓ Economical product
- ✓ Quick and Easy to install

SUITABLE FOR:



HUSH ACOUSTICS

TEL: 0151 933 2026

EMAIL: info@hushacoustics.co.uk

www.hushacoustics.co.uk

 [hush-acoustics](https://www.linkedin.com/company/hush-acoustics)

 [@hushacoustics](https://twitter.com/hushacoustics)  [hushuk.acoustics](https://www.facebook.com/hushuk.acoustics)

44 Canal Street, Bootle, Liverpool L20 8QU

Offices also based in London and Yorkshire



HUSH ACOUSTICS