

HUSH PANEL 17



Hush Panel 17 has been designed as a thinner overlay board to minimise floor build where required, without compromising performance. Hush-Panel 17 reduces impact sound transmission through separating floors, achieving excellent results. The upper layer of moisture resistant MDF provides a uniformly smooth surface for application of floor finishes.

ACOUSTIC PERFORMANCE

Impact $L'_{nT,w}$ dB	Airborne $D_{nT,w}$ dB	Airborne $D_{nT,w} + C_{tr}$ dB
47	57	50

Based on a recommended system incorporating Hush-Panel 17 over new floorboards



PRODUCT DATA

- Can be laid over existing or new concrete and timber floors.
- Comprises 9mm Moisture Resistant tongued and grooved MDF with 10mm Hushfelt™ resilient layer
- Overall Board Dimensions 1200mm x 600mm x 17mm
- Overall nominal thickness 19mm
- FFL over floor deck 17mm

SUITABLE FOR:



FEATURES

- ✓ Excellent acoustic performance
- ✓ Ideal for areas with limited room height
- ✓ Suitable for New Build, Change of Use and Refurbishment Projects
- ✓ Compatible with a range of Hush-Systems
- ✓ Can be used as part of a Code For Sustainable Homes compliant development
- ✓ Can be tiled over if used with Permalayer and a flexible adhesive
- ✓ Building Regulations Part E (England and Wales), Section 5 (Scotland) and Part G (Northern Ireland)
- ✓ Robust Details FFT5 compliant for floor structures EFC-1, EFC-2 and EFS-1

HUSH ACOUSTICS

TEL: 0151 933 2026

EMAIL: info@hushacoustics.co.uk

www.hushacoustics.co.uk

[hush-acoustics](https://www.linkedin.com/company/hush-acoustics)

[@hushacoustics](https://twitter.com/hushacoustics) [hushuk.acoustics](https://www.facebook.com/hushuk.acoustics)

44 Canal Street, Bootle, Liverpool L20 8QU
Offices also based in London and Yorkshire



HUSH ACOUSTICS