

HUSH-FELT 25 Resilient Strips

General

For Hush-Felt 25

Should you have any technical questions prior to or during installation, please call 0151 933 2026 for friendly and straightforward advice.

Sound insulation systems should be installed independently within each room.

To avoid plaster cracks and for good acoustic practice partition walls should only be built up from the structural base and not the floating floor. For ease of installation all structural bases should be level. Grout all joints, fill any gaps and thoroughly sweep the area before proceeding. If there is any likelihood of damp always lay a damp proof membrane over the structural slab.

Fixing the Hush-Felt 25

Joist tops should be levelled for best installation results.

Lay the strips end to end, hardboard pads upwards, and staple to the joist tops, using 16mm staples, through the gaps in the Hush-Felt 25. Do not fix, under any circumstances, through the hardboard pads.

Allow for a perimeter noggin at the end of the joist runs on to which is installed a length of Hush-Felt 25.

Fitting the Flooring

When planning the floor layout leave a 10-15mm gap around all perimeters.

Apply a snake of Hush-Bond Panel Adhesive on to each of the hardboard pads and lay the flooring boards on top in broken bond fashion. At the same time the flooring boards should be glued at all teegee joints board to board. Use no fixings whatsoever. Neatly press Hush-Seal 20 Perimeter Seal into the 10-15mm gap that has been left around all perimeters, creating an airtight seal.

Always try to avoid walking on the floor surface until all glue has cured.

Skirting should be fitted a minimum of three millimeters clear of the floor surface.

Technical Advice

For advice on the specification or use of Hush-Felt 25 within any project, please contact our experienced technical team on **0151 933 2026** who will be happy to give comprehensive and practical advice to meet with your requirements.